

The re-designed **Front Mount[™]** by **HydroHoist[®]** includes the all new positive-stop mooring kit. Featuring our patented buoyancy tank design, this hoist places significantly less dead load on the dock finger in the fully-lowered position. Our **Front Mount** Models are compatible with U-shaped slips, double-wide slips, and L-shaped moorings.



STANDARD FEATURES

- Hoist is available for inboard, pontoon, and tritoon boats
- Ultra-tough polyethylene tank
- Hot-dipped, zinc-galvanized structural steel and fasteners
- Grade 8 pivot hardware
- Adjustable hull support
- All cast parts are (HSLA) High-Strength Low Alloy steel
- No steel in the water
- Rugged adjustable mooring solution for multiple dock types

RECOMMENDED FOR:

- Boats up to 6,500 lbs and up to 28' in length
- Floating docks

OPTIONS INCLUDE:

- Bow Guide
- Plank Kit

TECHNICAL SPECS

Lift Size*	Weight of Lift (Lbs.)	Number of Main Tanks	Lift Width (ft)	Lift Length (ft/Inches)	Minimum Water Depth (ft/Inches)	Hull Bunk Length (ft)	Max. Beam of Boat (ft)	Max. Boat Length (ft)	Min. Slip Width
6500 SF	1550	1	8 ft.	23 ft., 2 in.	7 ft.	14 ft.	9 ft., 2 in.	26 ft.	9 ft.
6500 LF	1590	1	8 ft.	25 ft., 2 in.	7 ft., 10 in.	14 ft.	9 ft., 2 in.	26 ft.	9 ft.

*SF =Short Frame | *LF= Long Frame

BOATLIFT.COM

918.341.6811 | Fax: 918.341.1178

Email: sales@boatlift.com

915 West Blue Starr Drive ■ Claremore, OK 74017 USA